COMBINATION TABLE

MU4R25

Cooling															
Operation	Combination of Indoor Unit (kBtu/h Class)					Total Capacity						Input(W)		
						Min		Rated		Max				
	UNIT-A	UNIT-B	UNIT-C	UNIT-D	Total	Btu/h	kW	Btu/h	kW	Btu/h	kW	Min	Rated	Max
1 UNIT	5				5	3,600	1.06	5,000	1.47	6000	1.76	288	363	571
	7				7	4,200	1.23	7,000	2.05	8400	2.46	319	478	645
	9				9	5,400	1.58	9,000	2.64	10800	3.17	378	595	847
	12				12	7,200	2.11	12,000	3.52	14400	4.22	478	822	1139
	15				15	8,520	2.50	15,000	4.40	17040	4.99	573	1003	1356
	18				18	10,800	3.17	18,000	5.28	21600	6.33	747	1302	1827
2 UNIT	5	5			10	7,200	2.11	10,000	2.93	12000	3.52	350	532	788
	5	7			12	7,200	2.11	12,000	3.52	14400	4.22	350	669	991
	5	9			14	8,400	2.46	14,000	4.10	16800	4.92	408	821	1215
	7	7			14	8,400	2.46	14,000	4.10	16800	4.92	408	821	1215
	7	9			16	9,600	2.81	16,000	4.69	19200	5.63	469	991	1467
	5	12			17	10,200	2.99	17,000	4.98	20400	5.98	532	1083	1603
	9	9			18	10,800	3.17	18,000	5.28	21600	6.33	599	1182	1749
	7	12			19	11,400	3.34	19,000	5.57	22800	6.68	669	1290	1909
	5	15			20	12,000	3.52	20,000	5.86	24000	7.03	669	1406	2080
	9	12			21	12,600	3.69	21,000	6.15	24150	7.08	743	1530	2264
	7	15			22	13,200	3.87	22,000	6.45	25300	7.42	743	1638	2425
	5	18			23	13,800	4.04	23,000	6.74	26450	7.75	821	1752	2593
	9	15			24	14,400	4.22	24,000	7.03	27000	7.91	904	1871	2770
	12	12			24	14,400	4.22	24,000	7.03	27000	7.91	904	1871	2770
	7	18			25	14,400	4.22	24,000	7.03	27000	7.91	904	1871	2770
	9	18			27	14,400	4.22	24,000	7.03	27000	7.91	904	1871	2770
	12	15			27	14,400	4.22	24,000	7.03	27000	7.91	904	1871	2770
	5	24			29	14,400	4.22	24,000	7.03	27000	7.91	904	1871	2770
	12	18			30	14,400	4.22	24,000	7.03	27000	7.91	904	1871	2770
	15	15			30	14,400	4.22	24,000	7.03	27000	7.91	904	1871	2770
	7	24			31	14,400	4.22	24,000	7.03	27000	7.91	904	1871	2770
	9	24			33	14,400	4.22	24,000	7.03	27000	7.91	904	1871	2770
	15	18			33	14,400	4.22	24,000	7.03	27000	7.91	904	1871	2770
	18	18			36	14,400	4.22	24,000	7.03	27000	7.91	904	1871	2770
	12	24			36	14,400	4.22	24,000	7.03	27000	7.91	904	1871	2770
	15	24			39	14,400	4.22	24,000	7.03	27000	7.91	904	1871	2770
3 UNIT	5	5	5		15	9,000	2.64	15,000	4.40	18000	5.28	422	837	1239
	5	5	7		17	10,200	2.99	17,000	4.98	20400	5.98	481	1013	1500
	5	5	9		19	11,400	3.34	19,000	5.57	22800	6.68	544	1212	1794
	5	7	7		19	11,400	3.34	19,000	5.57	22800	6.68	544	1212	1794
	5	7	9		21	12,600	3.69	21,000	6.15	25200	7.39	682	1438	2128
	5	5	12		22	13,200	3.87	22,000	6.45	26400	7.74	731	1540	2279
	5	9	9		23	13,800	4.04	23,000	6.74	27600	8.09	731	1647	2437
	7	7	9		23	13,800	4.04	23,000	6.74	27600	8.09	731	1647	2437
	5	7	12		24	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	5	5	15		25	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	7	9	9		25	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	5	9	12		26	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	7	7	12		26	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	5	7	15		27	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	9	9	9		27	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	7	9	12		28	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	5	5	18		28	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	5	9	15		29	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	5	12	12		29	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	7	7	15		29	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	5	7	18		30	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	9	9	12		30	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	7	9	15		31	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	7	12	12		31	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	5	12	15		32	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	5	9	18		32	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	7	7	18		32	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	9	9	15		33	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	9	12	12		33	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	7	9	18		34	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	7	12	15		34	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	5	5	24		34	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	5	12	18		35	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	5	15	15		35	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	5	7	24		36	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	9	12	15		36	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	12	12	12		36	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	9	9	18		36	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	7	12	18		37	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	7	15	15		37	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	5	9	24		38	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	5	15	18		38	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	7	7	24		38	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	9	12	18		39	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	9	15	15		39	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603
	12	12	15		39	14,400	4.22	24,000	7.03	29000	8.50	837	1758	2603

※ For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.

COMBINATION TABLE

Cooling															
Operation	Combination of Indoor Unit (kBtu/h Class)					Total Capacity						Input(W)		
						Min		Rated		Max				
	UNIT-A	UNIT-B	UNIT-C	UNIT-D	Total	Btu/h	kW	Btu/h	kW	Btu/h	kW	Min	Rated	Max
4 UNIT	5	5	5	5	20	12,000	3.52	20,000	5.86	24000	7.03	592	1265	1872
	5	5	5	7	22	13,200	3.87	22,000	6.45	29000	8.50	659	1495	2212
	5	5	5	9	24	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	5	7	7	24	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	5	7	9	26	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	7	7	7	26	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	5	5	12	27	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	5	9	9	28	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	7	7	9	28	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	7	7	7	7	28	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	5	7	12	29	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	5	5	15	30	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	7	9	9	30	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	7	7	7	9	30	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	5	9	12	31	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	7	7	12	31	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	5	7	15	32	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	7	7	9	9	32	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	9	9	9	32	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	5	5	18	33	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	7	9	12	33	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	7	7	7	12	33	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	5	9	15	34	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	5	12	12	34	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	7	7	15	34	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	7	9	9	9	34	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	5	7	18	35	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	9	9	12	35	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	7	7	9	12	35	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	7	9	15	36	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	7	12	12	36	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	7	7	7	15	36	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	9	9	9	9	36	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	5	9	18	37	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	5	12	15	37	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	7	7	18	37	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	7	9	9	12	37	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	9	9	15	38	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	7	7	9	15	38	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	7	7	12	12	38	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	5	5	24	39	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	7	9	18	39	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	5	7	12	15	39	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	9	9	9	12	39	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603
	7	7	7	18	39	14,400	4.22	24,000	7.03	29000	8.50	731	1758	2603

COMBINATION TABLE

MU4R25

Heating															
Operation	Combination of Indoor Unit (kBtu/h Class)					Total Capacity						Input(W)		
						Min		Rated		Max				
	UNIT-A	UNIT-B	UNIT-C	UNIT-D	Total	Btu/h	kW	Btu/h	kW	Btu/h	kW	Min	Rated	Max
1 UNIT	5				5	4,000	1.17	5,500	1.61	6325	1.85	279	384	589
	7				7	5,040	1.48	8,400	2.46	9660	2.83	342	579	743
	9				9	6,480	1.90	10,800	3.17	12420	3.64	483	757	997
	12				12	7,920	2.32	13,200	3.87	15180	4.45	537	954	1234
	15				15	9,900	2.90	16,500	4.84	18975	5.56	688	1189	1593
	18				18	11,880	3.48	19,800	5.80	22770	6.67	845	1483	1978
	24				24	15,240	4.47	25,400	7.44	26670	7.82	1101	1840	2327
2 UNIT	5	5			10	7,200	2.11	12,000	3.52	14400	4.22	329	598	861
	5	7			12	8,640	2.53	14,400	4.22	17280	5.06	430	904	1301
	5	9			14	10,080	2.95	16,800	4.92	20160	5.91	484	945	1360
	7	7			14	10,080	2.95	16,800	4.92	20160	5.91	484	945	1360
	7	9			16	11,520	3.38	19,200	5.63	23040	6.75	540	1118	1610
	5	12			17	12,240	3.59	20,400	5.98	24480	7.17	598	1319	1899
	9	9			18	12,960	3.80	21,600	6.33	25920	7.60	660	1430	2059
	7	12			19	13,680	4.01	22,800	6.68	27360	8.02	725	1543	2221
	5	15			20	14,400	4.22	24,000	7.03	28800	8.44	764	1662	2393
	9	12			21	15,120	4.43	25,200	7.39	29000	8.50	793	1749	2518
	7	15			22	15,840	4.64	26,400	7.74	29000	8.50	867	1836	2644
	5	18			23	16,560	4.85	27,600	8.09	29000	8.50	945	1977	2850
	9	15			24	16,560	4.85	27,600	8.09	29000	8.50	945	1977	2850
	12	12			24	16,560	4.85	27,600	8.09	29000	8.50	945	1977	2850
	7	18			25	16,560	4.85	27,600	8.09	29000	8.50	945	1977	2850
	9	18			27	16,560	4.85	27,600	8.09	29000	8.50	945	1977	2850
	12	15			27	16,560	4.85	27,600	8.09	29000	8.50	945	1977	2850
	5	24			29	16,560	4.85	27,600	8.09	29000	8.50	945	1977	2850
	12	18			30	16,560	4.85	27,600	8.09	29000	8.50	945	1977	2850
	15	15			30	16,560	4.85	27,600	8.09	29000	8.50	945	1977	2850
	7	24			31	16,560	4.85	27,600	8.09	29000	8.50	945	1977	2850
	9	24			33	16,560	4.85	27,600	8.09	29000	8.50	945	1977	2850
	15	18			33	16,560	4.85	27,600	8.09	29000	8.50	945	1977	2850
	18	18			36	16,560	4.85	27,600	8.09	29000	8.50	945	1977	2850
	12	24			36	16,560	4.85	27,600	8.09	29000	8.50	945	1977	2850
	15	24			39	16,560	4.85	27,600	8.09	29000	8.50	945	1977	2850
3 UNIT	5	5	5		15	10,800	3.17	18,000	5.28	21600	6.33	497	946	1363
	5	5	7		17	12,240	3.59	20,400	5.98	24480	7.17	551	1118	1610
	5	5	9		19	13,680	4.01	22,800	6.68	27360	8.02	725	1419	2044
	5	7	7		19	13,680	4.01	22,800	6.68	27360	8.02	725	1419	2044
	5	7	9		21	15,120	4.43	25,200	7.39	30240	8.86	730	1610	2319
	7	7	7		21	15,120	4.43	25,200	7.39	30240	8.86	730	1610	2319
	5	5	12		22	15,840	4.64	26,400	7.74	31000	9.09	798	1697	2444
	5	9	9		23	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	7	7	9		23	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	5	7	12		24	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	5	5	15		25	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	7	9	9		25	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	5	9	12		26	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	7	7	12		26	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	5	7	15		27	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	9	9	9		27	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	7	9	12		28	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	5	5	18		28	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	5	9	15		29	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	5	12	12		29	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	7	7	15		29	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	5	7	18		30	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	9	9	12		30	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	7	9	15		31	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	7	12	12		31	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	5	12	15		32	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	5	9	18		32	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	7	7	18		32	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	9	9	15		33	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	9	12	12		33	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	7	9	18		34	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	7	12	15		34	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	5	5	24		34	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	5	12	18		35	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	5	15	15		35	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	5	7	24		36	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	9	12	15		36	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	12	12	12		36	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	9	9	18		36	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	7	12	18		37	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	7	15	15		37	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	5	9	24		38	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	5	15	18		38	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	7	7	24		38	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	9	12	18		39	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	9	15	15		39	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647
	12	12	15		39	16,560	4.85	27,600	8.09	31000	9.09	870	1838	2647

※ For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.

COMBINATION TABLE

Heating															
Operation	Combination of Indoor Unit (kBtu/h Class)					Total Capacity						Input(W)		
						Min		Rated		Max				
	UNIT-A	UNIT-B	UNIT-C	UNIT-D	Total	Btu/h	kW	Btu/h	kW	Btu/h	kW	Min	Rated	Max
4 UNIT	5	5	5	5	20	14,400	4.22	24,000	7.03	28800	8.44	700	1418	2041
	5	5	5	7	22	15,840	4.64	26,400	7.74	31000	9.09	795	1625	2339
	5	5	5	9	24	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	5	7	7	24	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	5	7	9	26	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	7	7	7	26	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	5	5	12	27	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	5	9	9	28	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	7	7	9	28	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	7	7	7	7	28	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	5	7	12	29	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	5	5	15	30	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	7	9	9	30	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	7	7	7	9	30	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	5	9	12	31	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	7	7	12	31	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	5	7	15	32	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	7	7	9	9	32	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	9	9	9	32	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	5	5	18	33	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	7	9	12	33	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	7	7	7	12	33	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	5	9	15	34	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	5	12	12	34	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	7	7	15	34	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	7	9	9	9	34	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	5	7	18	35	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	9	9	12	35	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	7	7	9	12	35	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	7	9	15	36	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	7	12	12	36	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	7	7	7	15	36	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	9	9	9	9	36	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	5	9	18	37	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	5	12	15	37	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	7	7	18	37	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	7	9	9	12	37	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	9	9	15	38	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	7	7	9	15	38	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	7	7	12	12	38	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	5	5	24	39	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	7	9	18	39	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	5	7	12	15	39	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	9	9	9	12	39	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647
	7	7	7	18	39	16,560	4.85	27,600	8.09	31000	9.09	832	1838	2647

COMBINATION TABLE

MU4R27

Cooling															
Operation	Combination of Indoor Unit (kBtu/h Class)					Total Capacity						Input(W)		
						Min		Rated		Max				
	UNIT-A	UNIT-B	UNIT-C	UNIT-D	Total	Btu/h	kW	Btu/h	kW	Btu/h	kW	Min	Rated	Max
1 UNIT	5				5	4,500	1.32	5,000	1.47	6,000	1.76	416	418	612
	7				7	4,800	1.41	7,000	2.05	8,400	2.46	416	494	663
	9				9	5,400	1.58	9,000	2.64	10,800	3.17	416	617	861
	12				12	7,200	2.11	12,000	3.52	14,400	4.22	494	846	1,153
	15				15	8,520	2.50	14,200	4.16	17,040	4.99	592	1,029	1,395
	18				18	10,800	3.17	18,000	5.28	21,600	6.33	769	1,328	1,804
	24				24	14,400	4.22	24,000	7.03	25,500	7.47	1,029	1,815	2,536
2 UNIT	5	5			10	6,000	1.76	10,000	2.93	12,000	3.52	378	623	853
	5	7			12	7,200	2.11	12,000	3.52	14,400	4.22	444	761	1,038
	5	9			14	8,400	2.46	14,000	4.10	16,800	4.92	533	903	1,228
	7	7			14	8,400	2.46	14,000	4.10	16,800	4.92	533	903	1,228
	7	9			16	9,600	2.81	16,000	4.69	19,200	5.63	601	1,047	1,423
	5	12			17	10,200	2.99	17,000	4.98	20,400	5.98	646	1,121	1,537
	9	9			18	10,800	3.17	18,000	5.28	21,600	6.33	692	1,195	1,623
	7	12			19	11,400	3.34	19,000	5.57	22,800	6.68	715	1,270	1,740
	5	15			20	12,000	3.52	20,000	5.86	24,000	7.03	761	1,347	1,829
	9	12			21	12,600	3.69	21,000	6.15	25,200	7.39	808	1,423	2,012
	7	15			22	13,200	3.87	22,000	6.45	26,400	7.74	855	1,475	2,154
	9	15			24	14,400	4.22	24,000	7.03	28,800	8.44	927	1,633	2,505
	12	12			24	14,400	4.22	24,000	7.03	28,800	8.44	927	1,633	2,505
	7	18			25	15,000	4.40	25,000	7.33	30,000	8.79	975	1,755	2,721
	9	18			27	16,200	4.75	27,000	7.91	31,050	9.10	1,047	2,011	2,891
	12	15			27	16,200	4.75	27,000	7.91	31,050	9.10	1,047	2,011	2,891
	5	24			29	16,200	4.75	27,000	7.91	31,050	9.10	1,047	2,011	2,891
	12	18			30	16,200	4.75	27,000	7.91	31,050	9.10	1,047	2,011	2,891
	15	15			30	16,200	4.75	27,000	7.91	31,050	9.10	1,047	2,011	2,891
	7	24			31	16,200	4.75	27,000	7.91	31,050	9.10	1,047	2,011	2,891
	9	24			33	16,200	4.75	27,000	7.91	31,050	9.10	1,047	2,011	2,891
	15	18			33	16,200	4.75	27,000	7.91	31,050	9.10	1,047	2,011	2,891
	18	18			36	16,200	4.75	27,000	7.91	31,050	9.10	1,047	2,011	2,891
	12	24			36	16,200	4.75	27,000	7.91	31,050	9.10	1,047	2,011	2,891
	15	24			39	16,200	4.75	27,000	7.91	31,050	9.10	1,047	2,011	2,891
3 UNIT	5	5	5		15	9,000	2.64	15,000	4.40	18,000	5.28	522	916	1,258
	5	5	7		17	10,200	2.99	17,000	4.98	20,400	5.98	607	1,054	1,445
	5	5	9		19	11,400	3.34	19,000	5.57	22,800	6.68	672	1,194	1,636
	5	7	7		19	11,400	3.34	19,000	5.57	22,800	6.68	672	1,194	1,636
	5	7	9		21	12,600	3.69	21,000	6.15	25,200	7.39	760	1,338	1,891
	7	7	7		21	12,600	3.69	21,000	6.15	25,200	7.39	760	1,338	1,891
	5	5	12		22	13,200	3.87	22,000	6.45	26,400	7.74	804	1,387	2,025
	5	9	9		23	13,800	4.04	23,000	6.74	27,600	8.09	826	1,461	2,219
	7	7	9		23	13,800	4.04	23,000	6.74	27,600	8.09	826	1,461	2,219
	5	7	12		24	14,400	4.22	24,000	7.03	28,800	8.44	871	1,535	2,379
	5	5	15		25	15,000	4.40	25,000	7.33	30,000	8.79	916	1,650	2,605
	7	9	9		25	15,000	4.40	25,000	7.33	30,000	8.79	916	1,650	2,605
	5	9	12		26	15,600	4.57	26,000	7.62	31,200	9.14	962	1,767	2,784
	7	7	12		26	15,600	4.57	26,000	7.62	31,200	9.14	962	1,767	2,784
	5	7	15		27	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	9	9	9		27	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	7	9	12		28	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	5	5	18		28	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	5	9	15		29	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	5	12	12		29	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	7	7	15		29	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	5	7	18		30	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	9	9	12		30	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	7	9	15		31	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	7	12	12		31	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	5	12	15		32	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	5	9	18		32	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	7	7	18		32	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	9	9	15		33	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	9	12	12		33	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	7	9	18		34	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	7	12	15		34	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	5	5	24		34	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	5	12	18		35	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	5	15	15		35	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	5	7	24		36	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	9	12	15		36	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	12	12	12		36	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	9	9	18		36	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	7	12	18		37	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	7	15	15		37	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	5	9	24		38	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	5	15	18		38	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	7	7	24		38	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	9	12	18		39	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	9	15	15		39	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	12	12	15		39	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	7	9	24		40	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	7	15	18		40	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	5	12	24		41	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784
	5	18	18		41	16,200	4.75	27,000	7.91	31,050	9.10	984	1,890	2,784

※ For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.

COMBINATION TABLE

Cooling															
Operation	Combination of Indoor Unit (kBtu/h Class)					Total Capacity						Input(W)		
						Min		Rated		Max				
	UNIT-A	UNIT-B	UNIT-C	UNIT-D	Total	Btu/h	kW	Btu/h	kW	Btu/h	kW	Min	Rated	Max
4 UNIT	5	5	5	5	20	12,000	3.52	20,000	5.86	24,000	7.03	680	1,202	1,633
	5	5	5	7	22	13,200	3.87	22,000	6.45	26,400	7.74	764	1,317	1,923
	5	5	5	9	24	14,400	4.22	24,000	7.03	28,800	8.44	827	1,458	2,215
	5	5	7	7	24	14,400	4.22	24,000	7.03	28,800	8.44	827	1,458	2,215
	5	5	7	9	26	15,600	4.57	26,000	7.62	31,200	9.14	913	1,679	2,520
	5	7	7	7	26	15,600	4.57	26,000	7.62	31,200	9.14	913	1,679	2,520
	5	5	5	12	27	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	5	9	9	28	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	7	7	9	28	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	7	7	7	7	28	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	5	7	12	29	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	5	5	15	30	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	7	9	9	30	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	7	7	7	9	30	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	5	9	12	31	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	7	7	12	31	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	5	7	15	32	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	7	7	9	9	32	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	9	9	9	32	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	5	5	18	33	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	7	9	12	33	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	7	7	7	12	33	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	5	9	15	34	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	5	12	12	34	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	7	7	15	34	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	7	9	9	9	34	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	5	7	18	35	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	9	9	12	35	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	7	7	9	12	35	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	7	9	15	36	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	7	12	12	36	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	7	7	7	15	36	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	9	9	9	9	36	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	5	9	18	37	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	5	12	15	37	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	7	7	18	37	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	7	9	9	12	37	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	9	9	15	38	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	7	7	9	15	38	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	7	7	12	12	38	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	5	5	24	39	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	7	9	18	39	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	7	12	15	39	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	9	9	9	12	39	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	7	7	7	18	39	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	7	9	9	15	40	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	7	9	12	12	40	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	5	7	24	41	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	9	12	15	41	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	5	12	12	12	41	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	7	7	12	15	41	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706
	7	7	9	18	41	16,200	4.75	27,000	7.91	32,400	9.50	935	1,795	2,706

COMBINATION TABLE

MU4R27

Heating															
Operation	Combination of Indoor Unit (kBtu/h Class)					Total Capacity						Input(W)		
						Min		Rated		Max				
	UNIT-A	UNIT-B	UNIT-C	UNIT-D	Total	Btu/h	kW	Btu/h	kW	Btu/h	kW	Min	Rated	Max
1 UNIT	5				5	5,000	1.47	5,500	1.61	6,325	1.85	610	610	714
	7				7	5,400	1.58	8,400	2.46	9,660	2.83	610	636	825
	9				9	6,480	1.90	10,800	3.17	12,420	3.64	610	826	1,077
	12				12	7,920	2.32	13,200	3.87	15,180	4.45	583	1,021	1,338
	15				15	9,900	2.90	16,500	4.84	18,975	5.56	744	1,279	1,744
	18				18	11,880	3.48	19,800	5.80	22,770	6.67	909	1,577	2,133
	24				24	15,240	4.47	25,400	7.44	26,670	7.82	1,192	2,077	2,538
2 UNIT	5	5			10	7,200	2.11	12,000	3.52	14,400	4.22	451	773	1,081
	5	7			12	8,640	2.53	14,400	4.22	17,280	5.06	541	940	1,337
	5	9			14	10,080	2.95	16,800	4.92	20,160	5.91	656	1,112	1,571
	7	7			14	10,080	2.95	16,800	4.92	20,160	5.91	656	1,112	1,571
	7	9			16	11,520	3.38	19,200	5.63	23,040	6.75	749	1,289	1,844
	5	12			17	12,240	3.59	20,400	5.98	24,480	7.17	796	1,392	1,968
	9	9			18	12,960	3.80	21,600	6.33	25,920	7.60	844	1,471	2,094
	7	12			19	13,680	4.01	22,800	6.68	27,360	8.02	892	1,577	2,222
	5	15			20	14,400	4.22	24,000	7.03	28,800	8.44	940	1,657	2,352
	9	12			21	15,120	4.43	25,200	7.39	30,240	8.86	989	1,766	2,568
	7	15			22	15,840	4.64	26,400	7.74	31,680	9.28	1,038	1,848	2,811
	5	18			23	16,560	4.85	27,600	8.09	33,120	9.71	1,112	1,960	3,127
	9	15			24	17,280	5.06	28,800	8.44	34,100	9.99	1,100	2,045	3,384
	12	12			24	17,280	5.06	28,800	8.44	34,100	9.99	1,100	2,045	3,384
	7	18			25	18,000	5.28	30,000	8.79	34,100	9.99	1,147	2,194	3,384
	9	18			27	18,600	5.45	31,000	9.09	34,100	9.99	1,194	2,157	3,384
	12	15			27	18,600	5.45	31,000	9.09	34,100	9.99	1,194	2,157	3,384
	5	24			29	18,600	5.45	31,000	9.09	34,100	9.99	1,194	2,157	3,384
	12	18			30	18,600	5.45	31,000	9.09	34,100	9.99	1,194	2,157	3,384
	15	15			30	18,600	5.45	31,000	9.09	34,100	9.99	1,194	2,157	3,384
	7	24			31	18,600	5.45	31,000	9.09	34,100	9.99	1,194	2,157	3,384
	9	24			33	18,600	5.45	31,000	9.09	34,100	9.99	1,194	2,157	3,384
	15	18			33	18,600	5.45	31,000	9.09	34,100	9.99	1,194	2,157	3,384
	18	18			36	18,600	5.45	31,000	9.09	34,100	9.99	1,194	2,157	3,384
	12	24			36	18,600	5.45	31,000	9.09	34,100	9.99	1,194	2,157	3,384
	15	24			39	18,600	5.45	31,000	9.09	34,100	9.99	1,194	2,157	3,384
3 UNIT	5	5	5		15	10,800	3.17	18,000	5.28	21,600	6.33	660	1,140	1,590
	5	5	7		17	12,240	3.59	20,400	5.98	24,480	7.17	748	1,309	1,850
	5	5	9		19	13,680	4.01	22,800	6.68	27,360	8.02	838	1,482	2,089
	5	7	7		19	13,680	4.01	22,800	6.68	27,360	8.02	838	1,482	2,089
	5	7	9		21	15,120	4.43	25,200	7.39	30,240	8.86	930	1,660	2,414
	7	7	7		21	15,120	4.43	25,200	7.39	30,240	8.86	930	1,660	2,414
	5	5	12		22	15,840	4.64	26,400	7.74	31,680	9.28	976	1,738	2,590
	5	9	9		23	16,560	4.85	27,600	8.09	33,120	9.71	1,046	1,842	2,767
	7	7	9		23	16,560	4.85	27,600	8.09	33,120	9.71	1,046	1,842	2,767
	5	7	12		24	17,280	5.06	28,800	8.44	34,560	10.13	1,093	1,922	2,951
	5	5	15		25	18,000	5.28	30,000	8.79	34,720	10.18	1,140	2,063	2,998
	7	9	9		25	18,000	5.28	30,000	8.79	34,720	10.18	1,140	2,063	2,998
	5	9	12		26	18,720	5.49	31,200	9.14	34,720	10.18	1,188	2,177	2,998
	7	7	12		26	18,720	5.49	31,200	9.14	34,720	10.18	1,188	2,177	2,998
	5	7	15		27	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	9	9	9		27	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	7	9	12		28	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	5	5	18		28	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	5	9	15		29	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	5	12	12		29	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	7	7	15		29	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	5	7	18		30	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	9	9	12		30	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	7	9	15		31	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	7	12	12		31	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	5	12	15		32	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	5	9	18		32	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	7	7	18		32	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	9	9	15		33	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	9	12	12		33	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	7	9	18		34	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	7	12	15		34	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	5	5	24		34	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	5	12	18		35	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	5	15	15		35	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	5	7	24		36	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	9	12	15		36	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	12	12	12		36	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	9	9	18		36	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	7	12	18		37	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	7	15	15		37	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	5	9	24		38	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	5	15	18		38	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	7	7	24		38	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	9	12	18		39	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	9	15	15		39	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	12	12	15		39	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	7	9	24		40	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	7	15	18		40	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	5	12	24		41	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998
	5	18	18		41	18,600	5.45	31,000	9.09	34,720	10.18	1,188	2,177	2,998

※ For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.

RESIDENTIAL
MULTI SPLIT

COMBINATION TABLE

Heating															
Operation	Combination of Indoor Unit (kBtu/h Class)					Total Capacity						Input(W)		
						Min		Rated		Max				
	UNIT-A	UNIT-B	UNIT-C	UNIT-D	Total	Btu/h	kW	Btu/h	kW	Btu/h	kW	Min	Rated	Max
4 UNIT	5	5	5	5	20	14,400	4.22	24,000	7.03	28,800	8.44	840	1,480	2,100
	5	5	5	7	22	15,840	4.64	26,400	7.74	31,680	9.28	927	1,651	2,470
	5	5	5	9	24	17,280	5.06	28,800	8.44	34,560	10.13	1,038	1,826	2,861
	5	5	7	7	24	17,280	5.06	28,800	8.44	34,560	10.13	1,038	1,826	2,861
	5	5	7	9	26	18,000	5.28	30,000	8.79	36,000	10.55	1,083	1,960	3,125
	5	7	7	7	26	18,000	5.28	30,000	8.79	36,000	10.55	1,083	1,960	3,125
	5	5	5	12	27	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	5	5	9	9	28	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	5	7	7	9	28	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	7	7	7	7	28	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	5	5	7	12	29	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	5	5	5	15	30	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	5	7	9	9	30	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	7	7	7	9	30	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	5	5	9	12	31	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	5	7	7	12	31	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	5	5	7	15	32	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	7	7	9	9	32	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	5	9	9	9	32	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	5	5	5	18	33	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	5	7	9	12	33	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	7	7	7	12	33	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	5	5	9	15	34	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	5	5	12	12	34	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	5	7	7	15	34	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	7	9	9	9	34	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	5	5	7	18	35	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	5	9	9	12	35	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	7	7	9	12	35	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	5	7	9	15	36	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	5	7	12	12	36	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	7	7	7	15	36	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	9	9	9	9	36	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	5	5	9	18	37	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	5	5	12	15	37	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	5	7	7	18	37	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	7	9	9	12	37	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	5	9	9	15	38	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	7	7	9	15	38	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	7	7	12	12	38	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	5	5	5	24	39	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	5	7	9	18	39	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	5	7	12	15	39	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	9	9	9	12	39	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	7	7	7	18	39	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	7	9	9	15	40	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	7	9	12	12	40	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	5	5	7	24	41	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	5	9	12	15	41	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	5	12	12	12	41	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	7	7	12	15	41	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125
	7	7	9	18	41	18,600	5.45	31,000	9.09	36,000	10.55	1,128	2,068	3,125